

## N-12<sup>®</sup> WT (WATERTIGHT) IB PIPE

It's a revolution that began nearly 15 years ago when ADS pioneered the watertight joint for corrugated polyethylene pipe. The ADS N-12 WT IB pipe – our third generation of watertight joint technology – is yet another leap forward in watertight performance.

The ADS N-12 WT IB pipe incorporates patented technology developed in the aerospace industry. A 2" wide proprietary ceramic/polymer composite is fused to the outside wall of the built-in bell, improving the joint's integrity and tolerance control. A patented gasket, that meets all requirements of ASTM F477, increases its sealing forces as internal or external hydrostatic pressure increases. Flared bell and spigot significantly improve ease of installation. N-12 WT IB pipe is so advanced in its design that it is easy to put your confidence in for long-term reliability.

### APPLICATIONS:

Storm Sewers	Culverts & Cross Drains
Sanitary Sewers	Slope/Edge Drains
Retention/Detention	Mining/Forestry/Industrial
Roof Drainage	Pond Overflows
Ditch Enclosures	

### FEATURES:

- 4" – 60" diameters available
- 6m (19 ft, 8 in) or 4m (13 ft) lengths available
- Built-in bell and factory-installed gasket
- Joint meets or exceeds ASTM D3212 lab test and ASTM F1417 watertight field test
- Exceptional joint strength
- Excellent abrasion and corrosion resistance
- Light weight
- Structural strength that will support H-25 live loads with 12" minimum cover and E-80 loads under 24" cover (60" pipe requires 2' cover for H-25 loads)

**ADS Service:** ADS representatives and engineers are committed to providing you with the answers to all your questions, including specifications, installation, backfill recommendations and more.



### BENEFITS:

- Variety of diameters and lengths fit any project
- Pipe requires no extra couplers, grout or other sealants for installation due to built-in bell and factory-installed gasket. This means fewer components to risk performance.
- Installation cost savings from lower shipping costs, fewer people, and less heavy equipment required.
- Hydraulic efficiency from smooth interior
- Long-term durability of HDPE



## ADS N-12® WT IB PIPE SPECIFICATION

### SCOPE

This specification describes 4- through 60-inch (100 to 1500 mm) ADS N-12 WT IB pipe for use in gravity flow drainage applications.

### PIPE REQUIREMENTS

N-12® WT IB pipe shall have a smooth interior and annular exterior corrugations.

- 4- through 10-inch (100 to 250 mm) shall meet AASHTO M252, Type S.
- 12- through 60-inch (300 to 1500 mm) shall meet AASHTO M294, Type S or ASTM F2306.
- Manning's "n" value for use in design shall be 0.012.

### JOINT PERFORMANCE

Pipe shall be joined with the N-12® WT IB joint meeting the requirements of AASHTO M294 or ASTM F2306.

The 4- through 60-inch (100 to 1500 mm) pipe shall be watertight according to the requirements of ASTM D3212. Gaskets shall meet the requirements of ASTM F477. Gaskets shall be installed by the pipe manufacturer and covered with a removable wrap to ensure the gasket is free from debris. A joint lubricant available from the manufacturer shall be used on the gasket and bell during assembly.

### FITTINGS

Fittings shall conform to AASHTO M252, M294 or ASTM F2306. Fabricated fittings shall be welded at all accessible interior and exterior junctions.

### MATERIAL PROPERTIES

Pipe and fittings shall be made of virgin polyethylene compounds that comply with the cell classification 424420C for 4- through 10-inch (100 to 250mm) diameters, or 435400C for 12- through 60-inch (300 to 1500mm) diameters, as defined and described in ASTM D3350. The 12- through 60-inch (300 to 1500mm) virgin pipe material shall comply with the notched constant ligament-stress (NCLS) test as specified in Section 6.1.1 and 5.1 of AASHTO M294 and ASTM F2306 respectively.

### INSTALLATION

Installation shall be in accordance with ASTM D2321 and ADS installation guidelines, with the exception that minimum cover in traffic areas for 4- through 48-inch (100 to 1200 mm) diameters shall be one foot (0.3 m) and for 60-inch (1500 mm) diameters, the minimum cover shall be 2 foot (0.6 m). Contact your local ADS representative or visit our website at [www.ads-pipe.com](http://www.ads-pipe.com) for a copy of the installation guidelines.

### PIPE DIMENSIONS

Pipe I.D., in. (mm)	Nominal Diameter, in (mm)												
	4 (100)	6 (150)	8 (200)	10 (250)	12 (300)	15 (375)	18 (450)	24 (600)	30 (750)	36 (900)	42 (1050)	48 (1200)	60 (1500)
Pipe O.D.*, in. (mm)	4.8 (122)	6.9 (175)	9.1 (231)	11.4 (290)	14.5 (368)	18 (457)	21 (559)	28 (711)	36 (914)	42 (1067)	48 (1219)	54 (1372)	57 (1702)
Perforations	All diameters available with or without perforations.												

\*Pipe O.D. values are provided for reference purposes only. values stated for 12- through 60-inch are ± 1 inch. Contact Applications Engineering for exact values.

For more information on ADS N-12 WT IB pipe and other ADS products, please contact our Customer Service Representatives at 1-800-821-6710

ADS "Terms and Conditions of Sale" are available on the ADS website, [www.ads-pipe.com](http://www.ads-pipe.com)  
The ADS logo, the Green Stripe, and N-12® are registered trademarks of Advanced Drainage Systems, Inc. © 2006 Advanced Drainage Systems, Inc.  
BRO 10582 08/06

